
ShinMaywa

SUCTION GULLY EMPTIER GRIT SWEEPER & CLEAN CUUM

SEWERAGE CLEANING SYSTEM



GRIT SWEEPER is a vacuum loader for waste fluid and sludge, and is equipped with high performance vacuum pump.






Specifications

·							
Model		GV2-V021	GV3-V021	GV4-V031	GV7-V031	GV11-V061	
Tank full volume		1,650L	2,600L	3,200L	6,700L	10,000L	
Vacuum system		Rotary vane type vacuum pump					
Vacuum	Pump capacity	3.1L	_/rev×1	5.2L/rev×1		5.2L/rev×2	
	Max.vacuum	-96kPa {-720mmHg}					
	Max.pressure	59kPa {0.6kgf/cm ² }					
Required PTO torque		196N·m {20kgf·m} or more		245N·m {25kgf·m} or more		392N·m {40kgf·m} or more	
Suitable shassis GVW		5,000~6,000kg	6,500~7,500kg	8,000~9,000kg	14,000~15,500kg	22,000~29,000kg	



CLEAN CUUM has powerful vacuum pump with strong air flow which is very efficient for suction at deeper and long distance.





Specifications

Model		GV4-W201C	GV7-W201C	GV11-W201C			
Tank full volume		3,200L	5,900L	10,500L			
Vacuum system		Roots blower					
Vacuum capacity	Max.air volume	24m³/min					
	Max.vacuum	-93kPa {-700mmHg}					
	Max.pressure	59kPa {0.6kgf/cm ² }					
	Dry sand	5,000kg/hour					
	Sewage	15,000kg/hour					
Required PTO torque		294N·m {30kgf·m} or more	343N·m {35kgf·m} or more	490N·m {50kgf·m} or more			
Suitable shassis GVW		8,000~9,000kg	14,000~15,500kg	22,000~29,000kg			

The above mentioned figures are approximate.

- *Optional equipment are included in these photographs.
- * Specifications and dimensions are subject to change without notice.

ShinMaywa Industries, Ltd.

International Sales Dept. Special Purpose Truck Div.

3-2-43, Shitte, Tsurumi-ku, Yokohama, 230-0003, Japan

Telephone: +81-45-575-5163 Facsimile: +81-45-575-9837 e-mail: overseas@shinmaywa.co.jp

